


Spindle Assemblies for Multiple Tapping Series 30000, 31000, 32000

Quality engineered spindles incorporate complete bearing construction with hardened spindles. Avaiable in stationary, adjustable and compensating designs. Complete assemblies include precision needle bearings for accuracy, thrust bearings for load, spindle complete with lock nut and wrenches if required, strong hex drive gear with tension adjusting nut, and positive single nut lock housing.




ORDER NUMBER	MODELS	TYPE	USE WITH COLLET SERIES	TAPPING CAPACITY	"C" LENGTH	NET WEIGHT
30405	2DS	#2 Collet Stationary 52600 #0 - 3/8" 4 1/8"		4 1/8"	3/4 lb.	
30406	5DS	#5 Collet Stationary	55600 55800	#0-3/8"	47/16"	3/4 lb.
30407	5DA	#5 Collet Adjustable Depth 7/8" Adj.	55600 55800	#0-3/8"	6 3/4" Max.	3/4 lb.
30408	5DC	#5 Collet Compression 1/2" Pitch Compression	55800	#0-3/8"	6 1/2"	3/4 lb.
30409	5DT	#5 Collet Tension 1/2" Pitch Compression	55800	#0-3/8"	5 11/16"	3/4 lb.

NOTE: Quick-change spindle assemblies are now available. Contact the factory for details.

SPECIFICAITONS

MODEL NO.	USE WITH TAPPER STYLE	BOLT CIRCLE CENTERS	CAPACITY					
			SOFT MATERIAL		STEEL		MAX. SPEED	SHIP
			THREAD	THREAD	THREAD	THREAD		WEIGHT
			CUTTING	FORMING	CUTTING	FORMING		
23 MD	3 - AL	1"-4"	#4 - 3/8"	#4 - 5/16"	#4 - 5/16"	#4 - 1/4"	1200	9 lbs.
33 MD	3 - AL	1 1/2" - 4 1/2"	#4 - 5/16"	#4-5/16"	#4 - 1/4"	#4-#12	1200	10 lbs.
43 MD	3 - AL	1 1/2" - 4 1/2"	#4 - 1/4"	#4-1/4"	#4-#12	#4-#12	1200	10 lbs.



625 McCue Rd, Suite 2, Lakeland, FL 33815 * Phone: 863-688-0071 * Fax: 863-682-6233 www.createch-design.com